

NEW

▲ Step-up

- ▲ 1.0 Megapixel Advanced HAD™ CCD Imager: 1070K Gross
1/6" Advanced HAD™ (Hole Accumulation Diode) CCD with 690K (effective) video pixels provides stunning detail and clarity, for exceptional video (up to 520 lines of horizontal resolution) and still image performance. Realize great looking digital still images with 1,000k effective pixels.
- 25X Optical/2000X Digital Zoom
The optical zoom helps to bring the action close up from far away. In addition, the Digital Zoom interpolation means that extreme digital zooming is clearer, with less distortion than previous types of digital zooms.
- Professional Quality Carl Zeiss® Vario-Tessar® Lens
Carl Zeiss lenses have an advanced optical multi-layer coating for increased contrast. This results in vivid image brilliance, true-to-life color saturation and perfect renditions of subtle tones.
- Handycam® Station
Simply placing the camcorder on the supplied Handycam Station cradle provides quick connections to a compatible TV for viewing or a PC for editing and sharing, all while charging the battery so your camcorder is always ready to go.
- ▲ 2.7" Wide (16:9) Touch Panel LCD Display (123K Pixels)⁴
The 2.7" Wide (16:9) LCD screen provides excellent viewing clarity. The high resolution 123K pixel LCD screen rotates up to 270 degrees for multiple viewing angles providing sharp, detailed images for monitoring or playback, and the widescreen format makes shooting in 16:9 mode and composing shots even easier.
- ▲ Memory Stick Duo™ Media Slot⁶
Capture still images up to 1152x864 resolution directly onto Memory Stick Duo media for easy transfer to PCs for emailing, printing or sharing with other compatible Memory Stick® media devices.
- ▲ One Touch Wide Angle Shooting
Easily switch between 16:9 and 4:3 aspect ratios for shooting, with just the touch of a button.
- ▲ Progressive Shutter System
A mechanical shutter system that provides progressive scan performance while utilizing an interlaced scanning system. Digital still images will be sharp and clear with excellent definition.
- Super SteadyShot® Picture Stabilization System
An advanced version of Sony's SteadyShot® system that controls an even higher range of shake and vibration frequencies, to achieve an even higher level of smoothness without degradation of video like some other image stabilization systems.
- USB 2.0 Interface³
USB 2.0 interface provides an easy way to connect your Hard Disk Handycam Camcorder to the computer for fast transfer of video and still images to your computer for editing. The camcorder can also be used as an external storage device, convenient for archiving, storing and transporting your videos and still images.
- DVDDirect® Compatibility
The DVDDirect system allows for easy transfer to a stand-alone DVD Burner via USB 2.0. The VRD-VC30 allows for easy transfer of video for DVD Burning. While the VRD-MC3 allows for seamless transfer of both Video and Still images for archiving on a DVD.
- Easy PC Backup
Easily back up your footage to your PC using the supplied software. The footage will be stored on your PC's hard drive for archiving purposes and viewing at a later time; the footage is stored by date allowing for quick access. In addition, only new footage is transferred to your PC each time you Backup your footage.
- One Touch Disc Burn
Easily burn a DVD copy of your footage using the supplied software. Simply connect you DCR-SR62 to your PC via the Handycam Station and supplied USB³ cable and press the One Touch Disc Burn button.
- HDD Smart Protection
A unique Shock Absorber protects the Hard Disk Drive from physical damage if the unit is dropped. When the 3G Sensor detects a drop (loss of gravity) the power to the Hard Disk Drive is turned off in order to prevent damage, during this time the DCR-SR62 remains powered on and recording video to the built-in buffer. Once the unit has recovered from the drop the buffer is then recorded to the Hard Disk Drive.
- ▲ Active Interface Shoe
Provides a location directly on the camcorder to which one may add optional accessories while providing power and two-way communication with those accessories.

ADDITIONAL FEATURES

- Super NightShot® Plus Infrared System
- Manual Focus
- On Screen Zoom and Record Buttons
- Scene Selection Modes
- Picture Effects
- Fader Effects
- InfoLITHIUM® Battery with AccuPower™ Meter System
- Battery Information
- Easy Handycam Button
- Tele Macro Function
- Multi-Language Menu



MEMORY STICK PRO DUO



DCR-SR62

Hard Disk Drive Camcorder - 30GB⁵

Specifications

General

Imaging Device: 1/6" Advanced HAD™ CCD
Pixel Gross: 1070K
Recording Media: 30GB⁵ Hard Disk Drive, Memory Stick PRO Duo™ Media (sold separately)
Recording and Playback Times: HQ: up to 7 hours, SP: up to 10 hours, LP: up to 20 hours
Video Actual: 670K Pixels (16:9), 690K Pixels (4:3)
Still Actual: 750K Pixels (16:9), 1000K Pixels (4:3)

Audio

Dolby® Digital Output: N/A
Recording System: Dolby Digital AC3 (2 Channel)

Convenience

USB Streaming: N/A
SteadyShot® Image Stabilization: Yes (Electronic)
Accessory Shoe: Yes (Active Interface Shoe)
White Balance: Auto, Indoor, One-push, Outdoor
Memory Stick PRO™ Media Compatibility: N/A
Still Image Mode(s): JPEG
Minimum Illumination: 4 Lux (0 Lux with Super NightShot® Plus Infrared System)
Low Light Capability: Super NightShot® Plus system

Convenience Features

Easy Operation: Yes
Fader Effects: Black, White
Multiple Language Display: Yes
Slide Show Mode: Yes
Tilting: N/A
Light/Flash: N/A
Scene Mode(s): Beach, Candle, Fireworks, Landscape, Portrait, Snow, Sports Lesson, Spotlight, Sunrise & Sunset and Twilight
Picture Effect(s): Monotone, Pastel and Sepia
Digital Picture Effect(s): Old Movie
PictBridge Compatible: Yes

Inputs and Outputs

Analog Audio/Video Input(s): N/A
Analog Audio/Video Output(s): Yes (Multi A/V)
Digital Audio/Video Input(s): Yes (via USB)
Digital Audio/Video Output(s): Yes (via USB)
USB Port(s): Yes: 2.0 Compliant (Handycam Station)³
i.LINK® Interface: N/A
Component Video (Y/Pb/Pr) Output(s): N/A
Headphone Jack: N/A
Microphone Input: Yes (via Active Interface Shoe)
Remote Jack: Yes
S-Video Input(s): N/A
S-Video Output(s): Yes (via optional accessory)
HDMI™ Connection Output(s): N/A

Hardware

LCD: 2.7" Wide (16:9) Hybrid Touch Panel SwivelScreen™ LCD Display (123K Pixels)⁴

Lens Type: Carl Zeiss® Vario-Tessar®

Sony Electronics Inc. • 16530 Via Esprillo • San Diego, CA 92127 • 1.800.222.7669 • www.sony.com

Docking Station: Yes (Handycam Station®)

Microphone: Yes (Built-in: Stereo)

Aperture: f1.8-3.2
Exposure: Yes; Touch Panel (32 steps)
Filter Diameter: 30mm
Focal Distance: 2.5-62.5mm; Telemacro Mode - 380mm
Focus: Full Range Auto/Manual (Touch Panel)
Progressive Shutter Mode: Yes
Shutter Speed: Auto, 1/60-1/4000 (Scene Selection Mode)
Optical Zoom: 25X
Digital Zoom: 200X
Resolution: 1MP

Power

Power Consumption: 3.0W (LCD)
Battery Type: InfoLITHIUM® with AccuPower™ Meter System (NP-FH40)

Service and Warranty Information

Limited Warranty: 1 Year Parts; 90 Days Labor

Software

Operating System Compatibility: Microsoft® Windows® 2000 Professional, XP Home, XP Professional
Supplied Software: Picture Motion Browser ver. 2.0

Video

Video Recording System: NTSC color, EIA standards
Analog-to-Digital Converter: Yes
Format(s) Supported: MPEG2 (SD)

Dimensions

Weight: 14 oz (400g) with supplied battery
Measurements: 2 7/8" x 2 7/8" x 4 5/8" (73x72x115mm)

Supplied Accessories

AC Power Adaptor/Camera Charger (AC-L200)
InfoLITHIUM® Rechargeable Battery (NP-FH40)
Remote Commander® Remote Control (RMT-835)
Handycam Station
A/V Cable (Stereo)
USB Cable
Enjoy Handycam DVD

Optional Accessories

High Grade A/V Cable with S-Video (VMC-30FS)
DVDirect - Video Only (VRD-VC30)

UPC Code: 027242712362

BATTERY LIFE¹

Battery ¹ (Fully charged)	Continuous Record Time LCD/LCD Bcklt Off	Continuous Playback Time LCD On/Off
NP-FH40	90/100 min	110/160 min
NP-FH50	105/115 min	130/180 min
NP-FH70	230/245 min	280/395 min
NP-FH100	525/565 min	635/890 min

STILL IMAGE MODE²

Fine/Standard Picture Quality

	1152x864 (4:3)	1152x648 (16:9)	640x480 (VGA)
30GB⁵ Hard Disk Drive	9999/9999	9999/9999	9999/9999
Memory Stick Duo™ Media⁶			
64MB	120/325	160/390	390/980
128MB	245/650	325/780	780/1970
Memory Stick PRO Duo™ Media⁶			
256MB	445/1150	590/1400	1400/3550
512MB	900/2400	1200/2850	2850/7200
1GB	1800/4900	2450/5900	5900/14500
2GB	3750/10000	5000/12000	12000/30000
4GB	7400/19500	9500/23500	23500/59000

1. Actual battery life may vary based on product settings, usage patterns, battery and environmental conditions. Designed for use with compatible Sony InfoLITHIUM® batteries.
2. Image size and files size may vary based upon the type and complexity of the image recorded.
3. Not all products with USB 2.0 connector may communicate with each other due to chipset variations.
4. Viewable area measured diagonally
5. 30GB means 30 billion bytes. Available storage capacity may vary and a portion of the memory is used for data management function.
6. Available storage capacity of Memory Stick and Memory Stick PRO media may vary. A portion of the memory is used for data management functions. Actual available memory in MBs is: 8MB=7.5, 16=15, 32=30, 64=61, 128=123, 256=220, 512=460, 1GB=940, 2GB=1.85GB, 4GB=3.66GB.

©2007 Sony Electronics Inc. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Sony, AccuPower, Advanced HAD, DVDirect, Handycam, InfoLITHIUM, like no other, NightShot, Remote Commander, SteadyShot and SwivelScreen are trademarks of Sony. Carl Zeiss and Vario-Tessar are trademarks of Carl Zeiss. PictBridge is a trademark of CIPA. Microsoft and Windows are registered trademarks of Microsoft Corporation. All other trademarks are property of their respective owners.
Features and specifications subject to change without notice. Non-metric weights and measures are approximate and may vary.
Screen Images Simulated

Please visit the Dealer Network for more information at
www.sony.com/dn

Last Updated: 12/07/2007